



NEW PRODUCT



Rough Red Tie Wire

Holds Strong. Stands Out Red.

Introducing Rough Red - Built for Strength and Visibility.

Rough Red is engineered for ironworkers and inspectors who won't compromise on performance. Featuring a high-visibility red HDPE coating with a robust textured finish that grips epoxy-coated rebar without sliding, superior hold strength, and the durability AWT is known for, Rough Red delivers faster inspections and more confident installs - job after job.



Key Advantages

Strong, Reliable Hold Soft annealed core ties smoothly and consistently for dependable performance.	Rugged AWT Finish Abrasion-resistant HDPE coating with a robust surface texture that grips epoxy-coated rebar and resists sliding during ties.
High-Visibility Red Coating Stands out against green epoxy rebar for faster, cleaner inspections.	100% Made in the USA Drawn, annealed, coated, and coiled domestically for guaranteed quality.

Specifications

Tensile Strength: 45,000–60,000 PSI	3# Coils, Packaged 20/BOX
C1006B, C1006, C1008 Soft Annealed	Conforms to ASTM A853 Specifications
Diameter: .062" +/- .002"	Coating: HDPE
Coating Diameter: .076 +/- .002", Core Wire Diameter: 0.062 +/- 0.002	

Scan Below for Details

Samples Available

Contact AWT to request Rough Red coils for evaluation or distributor programs.

